

VOLVO CONSTRUCTION A20 6x4 (Articulated Haulers)
Motor: D / DT Volvo TD71G148kW

Motor

- 1)NPL MAX 15W/40 (Max: 250 h)
- 2)NPL MAX 15W/40 (Max: 250 h)

Kraftöverföring

- 1)NPL MEX 15W/40 (Max: 1000 h)
- 2)NPL UTTO HT+ 10W/30 (Max 1000 h)

Hydraulik

- 1)NPL HYD ISO 46 (Max: 2000 h)
- 2)NPL HYD HVI 46 (Max: 2000 h)

Kylmedel

- 1)NPL GLYKOL OAT (Max: 2000 h)

Boggier

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAR OIL 80W/90 (Max: 2000 h)
- 3)NPL GEAR OIL LS 80W/90 (Max: 2000 h)

Fallådsväxel

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAR OIL 80W/90 (Max: 2000 h)
- 3)NPL GEAR OIL LS 80W/90 (Max: 2000 h)

Framaxel

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAR OIL 80W/90 (Max: 2000 h)
- 3)NPL GEAR OIL LS 80W/90 (Max: 2000 h)

Smörjpunkter

- 1)MATRIX EP2
- 2)CALIBER BLUE EP 2