

VOLVO CONSTRUCTION A25G Tier4f/Eu Stage4 (G - Series Articulated Haulers)
Motor: DT Volvo D11L, 10.8L, EGR+DOC+SCR; 234kW Årsmodell: 2014-

Motor

1)NPL MAX 15W/40 (Max: 500 h)

Hydraulik

1)NPL HS HYD HVI 46 ZF (Max: 4000 h)

Kylmedel

1)NPL GLYKOL OAT (Max: 6000 h, Max: 48 mån)

Bromskrets

1)NPL UTTO HT+ 10W/30 (Max: 4000 h)

Centralsmörjsystem

1)MATRIX EP 1

2)CALIBER BLUE HS 1

Fallådsväxel

1)NPL HS TRANS 75W/90 (Max: 4000 h)

Framaxel

1)PL HS TRANS 75W/90 (Max: 4000 h)

Boggiaxel fram

1)NPL HS TRANS 75W/90 (Max: 4000 h)

Smörjpunkter

1)MATRIX EP 2

2)CALIBER BLUE EP 2

Motorhuvens lyftkrets

1)NPL HS HYD HVI 46 ZF (Max: 4000 h)

Oljebad

1)NPL MAX 15W/40

Boggiaxel bak

1)NPL HS TRANS 75W/90 (Max: 4000 h)

Reduktionsnav

1)NPL HS TRANS 75W/90 (Max: 4000 h)

Upphängningscylinder

1)NPL HS HYD HVI 46 ZF (Max: 4000 h)