

VOLVO CONSTRUCTION A30 6x6 (Articulated Haulers)

Motor: Volvo TD102KH 214kW [DT]

Motor

- 1)NPL MAX 15W/40 (Max: 250 h)
- 2)NPL MEX 15W/40 (Max: 250 h)

Kraftöverföring

- 1)NPL MAX 10W/40 (Max: 500 h)
- 2)NPL MEX 15W/40 (Max: 500 h)
- 3)NPL UTTO HT+ 10W/30 (Max: 500 h)

Hydraulik

- 1)NPL HYD HVI 46 (Max: 2000 h)
- 2)NPL HS HYD HVI 46 ZF (Max: 2000 h)
- 3)NPL HYD HVI 68 (Max: 2000 h)

Kylmedel

- 1)NPL GLYKOL OAT (Max: 2000 h)

Fallådsväxel

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAROIL 80W/90 (Max: 2000 h)
- 3)NPL GEAROIL LS 80W/90 (Max: 2000 h)

Framaxel

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAROIL 80W/90 (Max: 2000 h)
- 3)NPL GEAROIL LS 80W/90 (Max: 2000 h)

Boggiaxel fram

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAROIL 80W/90 (Max: 2000 h)
- 3)NPL GEAROIL LS 80W/90 (Max: 2000 h)

Smörjpunkter

- 1)MATRIX EP 2
- 2)CALIBER BLUE EP 2
- 3)CALIBER BLUE HS 2

Boggiaxel bak

- 1)NPL HS TRANS 75W/90 (Max: 2000 h)
- 2)NPL GEAROIL 80W/90 (Max: 2000 h)
- 3)NPL GEAROIL LS 80W/90 (Max: 2000 h)